





**Wall Washers** 

Part No.	LED	Quantity	Color	Voltage	Power	IP Rating	PCB width	Viewing Angle	Unit Price ( USD)	
										>500reels
LR1011	SMD 5060	150-LED	RGB 3 in 1	12V DC	30-36W	IP20	5000x10x2.0mm	120°	\$165.00	\$136.00
LR1023	SMD 5060	300-LED	RGB 3 in 1	12V DC	60-72W	IP20	5000x12x2.0mm	120°	\$225.00	\$190.00
LR1020	SMD 5060	300-LED	RGB 3 in 1	24V DC	60-72W	IP20	5000x10x2.0mm	120°	\$225.00	190.60
New Type FIP66 (3M tape)Hot product										
LR7102	SMD 5050	150-LED/5m	PW/WW/R/G/B/Y	12V DC	30-36W	IP66	9mm		90.00	85.00
LR7121	SMD 5050	300-LED/5m	PW/WW/R/G/B/Y	24V DC	60-72W	IP66	9mm	120	125.00	100.00
LR7116	SMD 5060	150-LED/5m	RGB 3 in 1	12V DC	30-36W	IP66	9mm		175.00	155.00
LR7120	SMD 5060	300-LED5m	RGB 3 in 1	24V DC	60-72W	IP66	9mm		245.00	220.00
										E TE TE

## Let us help you design your system...FREE!!!











## Wall Washer


Salvin"s New 12 and 24 LED Second-Generation LED Wall Washer adopt 1W high power LED as light source. Main features include novel appearance, low consumption, long life span (fifty thousand hours average life), impact resistance, high reliability, environment-friendly, soft light, high brightness and brilliant colors. This new type of led wall washer is made up of two parts, the light housing and the power supply/ controller housing. What makes this wall washer unique too other wall washers is that this separation allows for a good heat-dissipating fixture, increasing LED life.

## LED Colors available are:

Single color units: Pure and warm white white, red, green, blue with a viewing angle of  $30^{\circ}$  and RGB color units: Viewing angel is  $50^{\circ}$ 

With it's ,built-in controller, 13 pre-programed light effect can be achieved. You may also connect a DMX controller for remote operation. DMX controller box to achieve the color change control in whole or segments ,such as red、green、blue、jump change、gradual , flicker etc. totally 14 types. It is with digital display window and control buttons to let the user to adjust stand-alone mode more for convenience. Calibrated brackets make aiming multiple units simple and easy.

The IP65 rating make the fixtures suitable for outdoor use.



The ir de rating make th	e iixtares saltable for catacor a		The total length of singnal wire is not more than 100 Meter each line The maximum connection number for each line is less than 20 pcs			
	Md #	Color	LED Qty	Voltage	IP Rating Dimentions	Price
	SAL4019	R/G/B	12x1W	100-240VAC	7" x 4.72" x 6.5" IP65 (179 x 120 x 165.3mm) 50° (including bracket)	\$285.00
	SAL4018	R/G/B	24x1W	100-240VAC	IP65 234.9 x 150 x 203.4mm <sup>50°</sup> (including bracket)	\$395.00
THE STATE OF THE S	SAL4020	PW/WW/R/G/B	12x1W	100-240VAC	IP65 7" x 4.72" x 6.5" 30° (179 x 120 x 165.3mm) (including bracket)	\$275.00
	SAL4021	PW/WW/R/G/B	24x1W	100-240VAC	IP65 234.9 x 150 x 203.4mm 20° (including bracket)	\$386.00